



# UNITED ATF DW-1

## Product Description

**Fully Synthetic Transmission oil specifically formulated to meet the needs of transmission system. It uses the finest additive that deliver the ideal friction properties for efficient shifting, economical transfer of power, and a smooth ride with exceptional performance. It is capable of maintaining consistent lubrication, prevent premature transmission failure, and protection against wear and corrosion. This resulting in extends the life of the transmission tool and reduces noise and vibration control.**

This product is suitable for use in HONDA DW-1 transmission.

## Applications / Benefits

- \* Ensuring smooth and precise gear shifts
- \* Prevents wear and corrosion
- \* Reducing the risk of blockages and malfunctions
- \* Excellent friction control at low temperature

## Typical Characteristics

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.839
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	25.04
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	6.897
Viscosity Index	ASTM D 2270	-	260



**United Oil**  
PERFORMANCE • VALUE • RELIABILITY

A member of the Repsol Group



## Specifications, Approvals & Recommendations

---

\* HONDA

DW-1

Reference No.  
5392G3ATFDW1REV0

Last revised date:  
28-08-24