



# UNITED ATF T-IV

## Product Description

**Premium Synthetic Automatic Transmission Fluid formulated with selected high viscosity index synthetic base stocks and latest additive technology available allowing very high performance needed for the demanding requirements of passenger cars' automatic gearboxes. This product can be used in a broad range of automatic transmissions and provides excellent service in a wide variety of North American, European, and Asian vehicles. It is particularly suitable for 4 and 5 speeds automatic transmissions.**

It is recommended for use in all GM vehicles DII, DIII(G), DIII(H). It exceeds the published JASO 1A, Ford M and Allison C-4 fluid specifications and suitable for use in automatic transmission recommending Toyota Type T-IV.

## Applications / Benefits

- \* Provide excellent oxidation and thermal stability for longer life
- \* Superior wear protection to protect critical transmission components
- \* Excellent viscosity stability (high VI), application in variety of auto transmission
- \* Excellent friction and anti-shudder performances

## Typical Characteristics

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.8551
Flash Point	ASTM D 92	°C	200
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	33.44
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	7.262
Viscosity Index	ASTM D 2270	-	190



**United Oil**  
PERFORMANCE • VALUE • RELIABILITY

A member of the Repsol Group



## Specifications, Approvals & Recommendations

---

\* ATF

T-IV

Reference No.  
4807G23ATFTIVREV0

Last revised date:  
23-01-24