



# UNITED MTA ULTRA 4T

## Product Description

Semi-synthetic motorcycle oil is a multigrade lubricant designed for four-stroke motorcycle engines. It contains a balanced blend of a specially selected synthetic base, high viscosity index base stocks and a special proprietary additive package. This oil is engineered to provide unsurpassed wear protection, engine cleanliness and oxidation resistance, as well as consistent

This oil is a powerful detergent type of motor oil. It can be used in most 4T engines including Yamaha, Honda, Kawasaki, Suzuki, and Kubota.

## Applications / Benefits

- \* Reduces engine wear and extends engine life
- \* Protects engine under severe operating conditions
- \* Retards harmful deposit formation on vital engine parts
- \* Protects against rust and corrosion

## Typical Characteristics

Test Description	Method	Unit	10W40	15W50
SAE Viscosity Grade	SAE J 300	-	<b>10W40</b>	<b>15W50</b>
Density @ 15 °C	ASTM D 4052	kg/L	0.861	0.871
Flash Point	ASTM D 92	°C	218	228
Pour Point	ASTM D 97	°C	-33	-27
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	97.33	151.9
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.77	19.56
Viscosity Index	ASTM D 2270	-	158	148
TBN	ASTM D 2896	mgKOH/g	7	7

## Specifications, Approvals & Recommendations

- \* API SP
- \* JASO MA2

Reference No.  
61209545G23SPMA2REV0

Last revised date:  
19/9/2023