



UNITED MWF SLIDEWAY OIL NT

Product Description

Hydrotreated Slideway Oil special formulated without tackifier for slideway application. This premium quality of lubricant is ashless, low odor, compounded lubricant. It offers outstanding demulsibility, oxidation stability, corrosion protection, lubricity, extreme pressure and anti-wear properties.

It is compatible with major metalworking fluids, reducing the risk of coolant performance issues in cases of contamination, and is also compatible with most elastomers while being non-corrosive to both ferrous and non-ferrous alloys.

Applications / Benefits

- * Protects against rust and corrosion
- * Outstanding lubricity, reduced friction
- * Excellent anti-oxidation property
- * Ashless and low odor

Typical Characteristics

| Test Description | Method | Unit | |
|-----------------------------|-------------|------|-----------|
| SAE Viscosity Grade | SAE J 300 | - | 68 |
| Density @ 15 °C | ASTM D 4052 | kg/L | 0.864 |
| Flash Point | ASTM D 92 | °C | 220 |
| Kinematic Viscosity @ 40°C | ASTM D 445 | cSt | 68.3 |
| Kinematic Viscosity @ 100°C | ASTM D 445 | cSt | 8.9 |
| Viscosity Index | ASTM D 2270 | - | 103 |

Reference No.
9525G2NONTCKSLIDEWAYREVO

Last revised date:
9/12/2025