



UNITED MX 2T SNOW PRO

Product Description

Synthetic 2T Motorcycle oil specifically formulated with high performance ester base oils and advanced additive technology to help provide high levels of engine cleanliness, minimize spark plug fouling, port blacking and scuff formation. It maximizes rust protection and pre-ignition for optimum performance power. It is suitable for all popular makes of air-cooled motorcycle engines, particularly high performance motorcycles with oil injection systems.

This product is suitable to use with pre-mixed petrol-oil or separate oil injection systems. Therefore, it can be introduced directly into the petrol tank with no prior mixing required. The petrol to oil ratio should be in accordance with the engine manufacturer's recommendations. This product contains special detergents that offer excellent protection against ring sticking.

Applications / Benefits

- * Outstanding engine cleanliness and high resistance to deposit formation
- * Excellent protection against ring sticking
- * Superior engine protection
- * Maximizes engine performance

Typical Characteristics

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.863
Flash Point	ASTM D 92	°C	120
Pour Point	ASTM D 97	°C	-42
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	51.12
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	8.488
Viscosity Index	ASTM D 2270	-	142

Specifications, Approvals & Recommendations

* API	TC
* JASO	FD (ISO L-EGD)