



UNITED MX RACING 2T

Product Description

Fully Synthetic 2T motorcycle oil designed to deliver superior protection for two-stroke gasoline engines. This advanced formulation ensures high levels of engine cleanliness and produces low smoke, minimizing issues such as spark plug fouling, port blocking and scuff formation. It also provides exceptional rust protection and reduces the risk of pre-ignition, optimizing performance and power output. This oil is suitable for popular air-cooled motorcycle engines, particularly high-performance motorcycles equipped with oil injection systems, and meets the requirements of engines designed for JASO FC performance standards.

This product is compatible with both pre-mixed petrol-oil or separate oil injection systems, allowing for direct introduction into the petrol tank without the need for prior mixing. The petrol-to-oil ratio should be maintained in accordance with engine manufacturer's recommendations.

Applications / Benefits

- * Effectively reduces exhaust smoke
- * Complete combustion, ensuring cleaner engine operation
- * Extended spark plug lifespan
- * Provides superior engine protection and maximizes performance

Typical Characteristics

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.8543
Flash Point	ASTM D 92	°C	106
Pour Point	ASTM D 97	°C	-33
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	41.5
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	7.602
Viscosity Index	ASTM D 2270	-	153



Specifications, Approvals & Recommendations

* API	TC
* JASO	FC

Reference No.
5375G35TCFCREVO

Last revised date:
06-01-24