



UNITED UC110

Product Description

Calcium Grease formulated with Calcium thickener, rust and oxidation inhibiting additives. It is a water-resistant, multi-purpose grease for heavy duty applications and is suitable for automotive and light truck chassis applications.

This grease is suitable for a wide variety of lubrication use. Recommended for motor vehicles & farm tractors chassis & suspension systems lubrication points, ball, shaft & universal joints and coil springs. Suitable for general automotive, industrial and agricultural lubrication of equipment, machine parts and automotive wheel bearings. Provides maximum protection against rust and corrosion for chassis that is susceptible to severe water exposure. Protects against moisture contamination with excellent water resistance. Prevents dust and dirt from contacting moving parts. This product is not recommended for low temperature application, the recommended operating temperature range is 15°C to 70°C

Applications / Benefits

- * Significant protection from severe water exposure
- * Longer vehicle component life due to low wear
- * Compatible with majority of greases used for chassis
- * Excellent resistance to water washout

Typical Characteristics

Test Description	Method	Unit	2.0	2.5	3.0
NLGI grade	-	-	2.0	2.5	3.0
Thickener type	-	-	Calcium soap	Calcium soap	Calcium soap
Appearance	Visual	-	Red	Red	Golden
Texture	-	-	Smooth	Smooth	Smooth
Worked Penetration	ASTM D 217	mm-1	265 - 295	250 - 265	220 - 250
Dropping point	ASTM D 2265	°C	100	100	155
Rust and Corrosion Test	ASTM D 1743	-	PASS	PASS	PASS
Water Wash-out	ASTM D 1264	-	PASS	PASS	PASS